

VERSYS-X 250



GREEN

Please note the image shown above is for illustration purposes only.

Specifications			
ENGINE		FRAME	
Type	Liquid-cooled, 4-stroke Parallel Twin, DOHC, 8 valves	Type	Backbone, high-tensile steel
Displacement	249 cm ³	Caster (rake)	24.3°
Bore and Stroke	62.0 x 41.2 mm	Tyre:	
Compression Ratio	11.3:1	a) Front	100/90-19M/C 57S
Performance:		b) Rear	130/80-17M/C 65S
a) Maximum power	24.7 kw {34PS} / 11,500 min ⁻¹	SUSPENSION	
b) Maximum torque	21.7 Nm {2.2 kgf.m} / 10,000 min ⁻¹	Front: Type	ø41 mm telescopic fork
Fuel System	Fuel injection: ø28mm x 2 with dual throttle valves	Rear: Type	Bottom-Link Uni-Trak, gas-charged shock and adjustable preload
Ignition	Digital	BRAKES	
Starting	Electric	Front: Type	Single ø290 mm petal disc
Lubrication	Forced lubrication, wet sump	Caliper	Single balanced actuation dual-piston
DRIVE TRAIN		Rear: Type	Single ø220 mm petal disc
Transmission	6 Speed, return	Caliper	Dual-piston
Gear ratios:		DIMENSIONS	
1st	2.600 (39/15)	Overall length	2170 mm
2nd	1.789 (34/19)	Overall width	860 mm
3rd	1.409 (31/22)	Overall height	1,390 mm
4th	1.160 (29/25)	Wheelbase	1,450 mm
5th	1.000 (27/27)	Ground clearance	180 mm
6th	0.893 (25/28)	Seat height	815 mm
Final reduction ratio	3.286 (46/14)	Curb mass	173 kg
Clutch	Wet multi-disc, manual	Fuel capacity	17 litres

Kawasaki Motors (Malaysia) Sdn. Bhd. reserves the right to alter specifications without prior notice.