

VN900 CUSTOM



Grey

Please note the above image(s) shown above is for illustration purposes only.

SPECIFICATIONS

ENGINE		FRAME	
Type	Liquid-cooled, 4-stroke V-Twin, SOHC, 8 valves	Type	Double-cradle, steel
Displacement	903 cm ³	Caster (rake)	33 °
Bore and Stroke	88.0 mm x 74.2 mm	Tyre:	
Compression ratio	9.5:1	a) Front	80/90-21M/C 48H
Performance:		b) Rear	180/70-15M/C 76H
a) Maximum power	40 kW {54 PS} 6,000 rpm	SUSPENSION	
b) Maximum torque	82 N.m {8.4 kgf.m} /3,500 rpm	Front: Type	41 mm telescopic fork
Fuel system	Fuel injection: ø34 mm x 2 with dual throttles	Rear: Type	Uni-Trak
Starting	Electric	BRAKES	
Ignition	Digital	Front: Type	Single 300 mm disc, Twin-piston
Lubrication	Forced lubrication (wet sump)	Rear: Type	Single 270 mm disc, Twin-piston
DRIVETRAIN		DIMENSIONS	
Transmission	5-speed, Return	Overall length	2405 mm
Gear ratios:		Overall width	895 mm
1st	2.786 (39/14)	Overall height	1120 mm
2nd	1.889 (34/18)	Wheelbase	1645 mm
3rd	1.360 (34/25)	Ground clearance	140 mm
4th	1.107 (31/28)	Seat height	685 mm
5th	0.963 (26/27)	Curb mass	278 kg
6th	-	Fuel capacity	20 litres
Final reduction ratio	2.063 (66/32)		
Clutch	Wet multi disc, Manual		

Kawasaki Motors (Malaysia) Sdn. Bhd. reserves the right to alter specifications without prior notice.